

TD Delphinus Series

Handheld Thermal Imaging Monocular

High Cost-Effective Scope For Every Explorer



Introduce

TD Delphinus Series follow the design of traditional optical equipment. It is a small, lightweight, simple operation, and a wide range of application scenarios for infrared handheld thermal imaging monocular. TD Thermal scope has clear imaging and comfortable observation, suitable for medium-distance and short-distance observation, It is an ideal equipment for outdoor night vision.



Features and Benefits

- o Boot up in 2 seconds and ready to use
- o High-sensitivity self-developed infrared detector to accurately detect targets
- o Built-in laser indicator to locate the target easily
- o 1280x960 High Resolution LCOS Display Screen to provide a comfortable observation
- o PIP mode to Highlight Target Clearly
- o Connect App via WIFI to share anytime
- o Support 8 hours super long operation time
- o IP66 Encapsulation, Rugged and Durable

Application

- o Outdoor
- o Wild Adventure
- o Law Enforcement
- o Search & Rescue
- o Personal Security
- o Livestock Breeding

Specifications

| Product model | TD210 | TD410 | TD420 | TD430 |
|---------------------------|---|------------------|-------------|-------------|
| Infrared Detector | | | | |
| Detector type | VOx | | | |
| Detector resolution | 256 × 192, 12 μm | 400 × 300, 12 μm | | |
| Spectral range | 8 to 14 μm | | | |
| NETD | ≤50mk | ≤40mk | | |
| Frame rate | 50 Hz | | | |
| Lens | | | | |
| Focal length | 10 mm; F1.0 | 19 mm; F1.0 | 25 mm; F1.1 | 35 mm; F1.0 |
| Focus | Electric | Manual | | |
| Field of view | 17.1°×13.0° | 13.6°×10.3° | 10.4°×7.9° | 7.5°×5.6° |
| Optical zoom | 1.5x | 1.9x | 2.4x | 3.4x |
| Digital zoom | 1x, 2x | 1x, 2x and 4x | | |
| Power | | | | |
| Battery type | Single, replaceable 18650 battery | | | |
| Battery life | ≥ 8 hours | ≥ 7 hours | | |
| Interface | | | | |
| USB | Type C (USB 2.0 standard), supporting analog video and power supply | | | |
| Video interface | USB Type C | | | |
| External expansion | External Display and Bluetooth remote control | | | |
| Mechanical interface | UNC ¼"-20 (Tripod mounting), Mechanical expansion interface | | | |
| Display | | | | |
| Display type | 0.4" FLCOS | | | |
| Resolution | 1280 × 960 | | | |
| Eyepiece | Monocular, exit pupil distance ≥12 mm, diopter adjustment: -4 to + 2 | | | |
| Eyepiece zoom | 13.8x | | | |
| Video output | Analog video | | | |
| Functions | | | | |
| PIP | Upper left, Upper middle, Upper right, Closed | | | |
| Image enhancement | Supported only when there is no laser indicator | | | |
| Scene modes | Enhanced, Highlight and Natural | | | |
| Ultra power saving mode | Turn WIFI off or reduce the screen brightness level | | | |
| WIFI | Transmission of real-time video via WIFI for remote control in the 2.4G frequency band and within 15 meters | | | |
| Color palettes | Black Hot, White Hot, Red Hot, Iron Hot, Blue Hot | | | |
| Hot spot tracking | Available | | | |
| Compensation modes | Automatic, shutter and scene compensation | | | |
| Laser | Supported only when a laser indicator is available, up to 200 m | | | |
| System | | | | |
| Language settings | Chinese or English | | | |
| Start up | 1 s | 2 s | | |
| Environmental | | | | |
| Storage temperature range | -30 °C to 60 °C | | | |
| Humidity | 10 % to 95 % non-condensing | | | |
| Shock | 30 G at 11 ms half sine pulse (as per IEC60068-2-27) | | | |
| Vibration | 10 Hz~150 Hz~10 Hz 0.15 mm (as per IEC60068-2-6) | | | |
| Drop | 1 m | | | |
| Encapsulation | IP66 | | | |
| Certification | IP66, FCC, CE, RoHS, EAC, WEEE, un38.3, IEC 60825-1 Class 2 | | | |
| Physical | | | | |
| Weight | ≤280 g | ≤350 g | | |
| Size (L × W × H) | 130 × 40 × 70 mm | 150 × 40 × 70 mm | | |
| Standard | Battery charger (for China, US, UK, Australia and Europe and in compliance with FCC, CE, EAC and RoHS), single 18650 battery, USB Type C cable, lens cap, wrist strap, carry bag, quick start guide | | | |
| Optional | Extended bracket | | | |

Specifications

