

TU Gen2


Thermal Imaging Scope

Unlock Hidden Detail with HD AMOLED Display



Introduction

The TU Gen2 Series is equipped with a high-sensitivity thermal sensor of 12 μ m and a 1440 \times 1080 HD AMOLED display. Paired with the robust PureIR image algorithm, it provides users with a more vivid and detailed visual experience. The product has undergone meticulous optimization in its detailed design, elevating user-friendly operation. Furthermore, the battery life has seen a substantial extension, resulting in a 20% increase in duration.



Features and Benefits

- HD AMOLED display for higher image quality and reduced visual fatigue
- The PureIR algorithm for high-sensitivity thermal images
- Super long battery life of up to 12 hours
- OTA firmware upgrade by connecting to the APP
- Photo and video recording to keep the best moments
- IP67 encapsulation, resistant to 800G shock
- User-friendly improved left-hand operation experience and optimized opening direction of USB cover

Applications

- Night hunting
- Law enforcement
- Search & Rescue
- Personal security

Specifications

| Product model | TU431 | TU451 | TU631 | TU651 |
|--------------------------|---|-------------|---------------------|-------------|
| Sensor | | | | |
| Type | Uncooled VOx Infrared Detector, 8 to 14 μ m | | | |
| Resolution | 400×300, 12 μ m | | 640×480, 12 μ m | |
| NETD | \leq 30mK | | | |
| Frame rate | 50 Hz | | | |
| Lens | | | | |
| Focal length | 35 mm, F1.0 | 50 mm, F1.0 | 35 mm, F1.0 | 50 mm, F1.0 |
| Field of angle | 7.8°×5.9° | 5.5°×4.1° | 12.5°×9.4° | 8.8°×6.6° |
| Optical zoom | 2.65x | 3.78x | 1.65x | 2.36x |
| Digital zoom | 1x ~ 4x | | 1x ~ 8x | |
| Focus | Manual | | | |
| Display | | | | |
| Display type | 0.39" AMOLED | | | |
| Resolution | 1440×1080 | | | |
| Eyepiece | Exit pupil distance \geq 48 mm; Diopter \pm 4; Zoom: 14x | | | |
| Video output | Digital video | | | |
| Range Performance | | | | |
| Detection range | 1000 m | 1400 m | | 2000 m |
| Functions | | | | |
| Scene modes | Enhanced, Highlight and Natural | | | |
| Color palettes | White Hot, Black Hot, adjustable Red Hot, Green Hot, Iron Red, Blue Hot | | | |
| Recording function | Photo/Video | | | |
| WIFI | 2.4G | | | |
| Supported Application | TargetIR | | | |
| Firmware OTA | Upgrade device firmware via app connection | | | |
| Others | PIP, Hot spot tracking, Rough ranging | | | |
| Power | | | | |
| Battery type | Single 18650 battery (built-in) and customized battery (external) | | | |
| Operating time | \geq 12 hours | | | |
| Interface | | | | |
| USB | USB Type-C | | | |
| Video interface | micro HDMI | | | |
| Mechanical interface | Picatinny | | | |
| Tube diameter | Standard 30 mm | | | |
| System | | | | |
| Language settings | English / Russian / German / French / Italian / Spanish / Japanese / Korean / Polish | | | |
| Memory capacity | 128GB | | | |
| Environmental | | | | |
| Operating temperature | -30°C to 50°C | | | |
| Storage temperature | -40°C to 70°C | | | |
| Humidity | 10 % to 95 % non-condensing | | | |
| Shock | 800 G at 1 ms half sine pulse (as per IEC60068-2-27) | | | |
| Encapsulation | IP67 | | | |
| Certification | FCC, CE, RoHS, EAC, un38.3 | | | |
| Physical | | | | |
| Weight | \leq 990g (without eye mask and battery) | | | |
| Size | \leq 377×107×69 mm (without eye mask) | | | |
| Standard | Device, lens cap, eye mask, 5V2A adapter (US, Britain, Australia and Europe), Desktop charger, customized battery×2, Extended clip×2, USB Type-C cable, micro HDMI cable, Quick start guide | | | |
| Optional | Bluetooth remote control, Customized battery, Extended bracket | | | |